

### REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1-11 in the underlying PCT Application No. PCT/DE03/00463 and adds new claims 12-23. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter). The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/00463 includes an International Search Report, dated July 23, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

*by [Signature] (revised 3/6/91)*

Dated: 3 Sept 2004

By: [Signature]  
Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, NY 10004  
(212) 425-7200  
(212) 425-5288

CUSTOMER NO. 26646

[10191/3775]

# SENSOR SYSTEM

## ~~Background Information~~ FIELD OF THE INVENTION

The present invention ~~starts out from~~ relates to a sensor system ~~according to the preamble of Claim 1.~~

## 5 ~~In known~~ BACKGROUND INFORMATION

In conventional sensor configurations, e.g., lambda probes for measuring oxygen concentration in exhaust gas from internal combustion engines, exact measured-value acquisition requires the protruding end of the measuring  
10 element or sensor that is immersed in the test gas and is located on the test gas side to be aligned in a predefined manner relative to the gas flow. This alignment is performed on-site during assembly.

15 In the case of a ~~known~~ conventional sensor system of this type~~(, as described in~~ German Patent Application No. DE 43 18 107 A1~~)~~, such an alignment of a lambda probe relative to the exhaust-gas flow is performed during assembly so that a gas inflow opening formed in a protective pipe covering the  
20 protruding end of the measuring element on the test gas side is located on the side away from the exhaust-gas flow. As a result, condensation water included in the exhaust gas is not able to reach the protruding end of the measuring element, is not able to deposit there, and is consequently  
25 not able to affect the measuring accuracy of the lambda probe. To always ensure correct alignment of the lambda probe during installation in the exhaust-gas pipe in a reproducible manner regardless of the qualifications of the on-site assembler, an assembly aid is provided such that a  
30 marking indicating the position of the gas inflow opening on

the protective pipe is made on a metal sleeve that is  
fixedly connected to the housing and covers a  
connection-side protruding end of the measuring element that  
protrudes from the housing. This marking allows the sensor  
5 to be inserted into the receiving element on the exhaust-gas  
pipe such that the gas inflow opening in the protective pipe  
points in the exhaust-gas flow direction. After the lambda  
probe achieves an orientation coordinated with the  
exhaust-gas flow direction, the housing is tightened via a  
10 union nut in a receiving element that is attached to the  
exhaust-gas pipe and that accommodates the housing. It is  
proposed as an alternative assembly aid to provide the  
sensor housing with such a geometry that assembly is only  
possible with the desired alignment of the lambda probe via  
15 a form-locking means- arrangement.

~~Summary of the Invention~~ SUMMARY

~~The An example~~ sensor system of the present invention ~~having~~  
~~the features of Claim 1 has~~ may have the advantage that the  
20 performed fixing of the piercing points starting points of  
the threads in the two parts to be screwed together, namely  
the housing and the receiving element, and the stipulated  
tightening torque makes it possible to always produce the  
correct position of the measuring element regardless of  
25 assembly. Since the housing itself is screwed into the  
receiving element, additional elements, e.g., a union nut,  
for fixing the sensor in the receiving element that are  
considered to be losable parts are rendered unnecessary.

30 According to an advantageous embodiment of the present  
invention, a marking is situated on the housing that  
specifies an orientation for the installation of the  
measuring element and is oriented with respect to the  
piercing point of the outside thread on the housing. Since

the housing is completed with external housing during manufacture of the sensor, the marking oriented with respect to the piercing point of the threads, e.g., a simple radial blind hole in the housing, ensures prior to insertion of the measuring element that the measuring element is inserted into the housing with the correct alignment.

~~The~~ An example embodiment of a sensor system of according to the present invention having the features of Claim 4 has ~~may~~ have the advantage that the necessary alignment of the sensor in the receiving element is able to be ensured for an existing sensor design having hollow screw fixing of the sensor in the receiving element by simply minimally changing the manufacturing method and without changing the sensor itself. In particular, when the projection is achieved according to advantageous embodiments of the present invention by an insertion ring pressed tightly against the housing or an insertion pin inserted radially into the housing, a structural change is only required for the sensor receiving element with respect to the axial groove to be cut on the front side.

~~Brief Description of the Drawing~~ BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is explained ~~more closely~~ in further detail in the exemplary embodiments shown in the ~~drawing~~ figures and in the following description.

~~The figures schematically show:~~

Figure 1 shows a side view of a sensor system, partially cut.

Figure 2 shows a top view of an insertion ring in the sensor

system of Figure 17.

Figure 3 shows a longitudinal section of the sensor system in Figure 17.

Figure 4 shows an enlarged representation of the section IV in Figure 37.

Figure 5 shows an enlarged representation of the section V in Figure 37.

Figure 6 shows the same representation as in Figure 5 with a modification to the sensor system.

Figure 7 shows a side view of a sensor system according to a further exemplary embodiment, partially cut.

#### ~~Description of the Embodiments~~ DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

The sensor system shown in Figures 1 and 3 has a sensor 10 for measuring a gas parameter of a test gas, shown as a side view in Figure 1 and as a longitudinal section in Figure 3, and a test-gas line 11, through which a test gas flows, shown sectionally as a cross section in Figures 1 and 3. In the example in Figures 1 and 3, sensor 10 is a lambda probe for measuring oxygen concentration as the gas parameter in the exhaust gas of an internal combustion engine, and test-gas line 11 is an exhaust-gas pipe outgoing from one or more combustion cylinders of the internal combustion engine.

Sensor 10 has a sensor or a measuring element 13 (Figure 3), which is accommodated in a housing 12 and protrudes therefrom at a section 131 on the test gas side and a

section 132 on the connection side. In this context, measuring element 13 is surrounded by an electrically insulating ceramic insert 14 on the test gas side, an electrically insulating ceramic insert 15 on the connection side, and an interposed, packet-like seal 16, which is supported by the inner wall of housing 12. Ceramic insert 14 on the test gas side lies on a shoulder 17 on the inner housing wall, and the top housing edge is flared to ceramic insert 15 on the connection side. In an alternative embodiment, ceramic insert 15 on the connection side lies on a shoulder formed in housing 12, and the bottom housing edge is flared to ceramic insert 14 on the test gas side. As shown, the packet-like seal may be made up of three stacked sealing elements, the two external ones being made of steatite, for example, and the middle one being made of boron nitride. A metal sleeve 18, which covers an electrical clamp connector 19, which contacts connection-side section 132 of measuring element 13 and a connecting wire 20, is placed on housing 12. A protective pipe 21, which covers section 131 of measuring element 13 on the test gas side, is pushed onto the end of housing 12 facing away from metal sleeve 18. There are gas inflow openings 22 in protective pipe 21 so that after installation of sensor 10 in test-gas line 11, the test gas flowing in test-gas line 11 is able to flow through gas inflow openings 22 to measuring element 13. To mount sensor 10 on test-gas line 11, housing 12 is provided with a radial flange 23, which is beveled on the underside, and a hollow screw 24, which acts together with radial flange 23, is provided.

Test-gas line 11 has a sensor insertion opening 25, which is incorporated into line wall 111, and a receiving element 26 for housing 12 of sensor 10, which surrounds sensor insertion opening 25 and is attached to line wall 111.

Receiving element 26 has a beveled support shoulder 27 for radial flange 23 of housing 12 and an internal thread 28, which corresponds with the external thread of hollow screw 24. As shown in Figures 1 and 3, receiving element 26 may be

5 configured as a hollow connecting piece that is inserted into an expanded sensor insertion opening 25 in line wall 111 and is welded circumferentially to line wall 111.

However, the hollow connecting piece may also be positioned on line wall 111 to surround sensor insertion opening 25 and

10 welded with line wall 111.

During assembly of the sensor system, sensor 10 including its housing 12 is inserted into receiving element 26 at test-gas line 11, protective pipe 21 penetrating sensor

15 insertion opening 25 into the interior of test-gas line 11, and housing 12 pushing so far into receiving element 26 that the beveled underside of radial flange 23 contacts beveled support shoulder 27 in receiving element 26. Hollow screw 24 is then pushed over metal sleeve 28 and housing 12 and

20 screwed into internal thread 28 of receiving element 26 until its annular end face tightens radial flange 23 to support shoulder 27.

The accurate measuring function of sensor 10 requires

25 section 131 of measuring element 13 on the test gas side projecting into the gas flow and surrounding protective pipe 21 to achieve a certain alignment within the test-gas flow. An assembly aid having an allocation element situated on housing 12 and oriented with respect to the installation

30 position of measuring element 13 and an allocation element situated at receiving element 26 and oriented with respect to the test-gas flow is provided to ensure that the alignment is reproducible. In the exemplary embodiment in Figures 1-5, the allocation element disposed at receiving



element 26 is an axial groove 29, which runs in the region of internal thread 28 and runs out freely on the front side, and the allocation element formed at housing 12 is a projection 30, which projects radially over the housing periphery, slides in a positive-locking manner in axial groove 29 when housing 12 is inserted into receiving element 26, and prevents rotation of sensor 10 about its axis. As Figure 2 shows in particular, projection 30 is a one-piece part of an insertion ring 31, which lies on the flange surface of radial flange 23 facing hollow screw 24 and is fixedly connected to housing 12, preferably pressed against housing 12. Insertion ring 31 is pressed against housing 12 in that projection 30 is oriented with respect to the predetermined installation position of measuring element 13 in housing 12. In addition, housing 12 may have a flat section 121 at its periphery, and insertion ring 31 may be bent in its ring region 311, which is assigned to flat section 121, such that ring region 311 lies flat against flat section 121 (Figures 2 and 5). Bent ring region 311 is preferably positioned at insertion ring 31 such that it is diametrically opposed to projection 30 (Figures 1-3). When installing measuring element 13 in housing 12, flat section 121 is used to align measuring element 13 with respect to housing 12 in that measuring element 13 is oriented such that it has a certain rotation position with respect to flat section 121 of housing 12. If insertion ring 31 is then pushed onto housing 12, projection 30 has the desired orientation with respect to the alignment of measuring element 13 in housing 12.

Although not shown in greater detail, projection 30 may also be formed on housing 12 as one piece.

In the modification of the sensor system shown in Figure 6,

projection 30 is formed by an insertion pin 32, which is pressed into a radially formed blind hole 33 in housing 12. The part of insertion pin 32 protruding from blind hole 33 forms projection 30, which projects in a positive-locking manner into axial groove 29 in the groove width as described above.

In the sensor system shown in Figure 7, the design of sensor 10 is modified to the extent that the hollow screw for fixing housing 12 in receiving element 26 is dispensed with, and housing 12 has its own external thread 34 as well as a hexagon 35 for screwing housing 12 into internal thread 28 of receiving element 26. To achieve the allocation elements at housing 12 and receiving element 26 for the purpose of exact alignment of measuring element 13 in test-gas line 11, the piercing point of external thread 34 at housing 12 is oriented with respect to the installation position of measuring element 13 in housing 12 and the piercing point of internal thread 28 in receiving element 26 is oriented with respect to the test-gas flow. This configuration of the piercing points of threads 28 and 34 allows housing 12 to always be screwed from only one specific rotation position about its longitudinal axis into receiving element 26. If a predefined tightening torque is additionally applied to hexagon 35 following complete screwing in of housing 12, measuring element 13 is aligned in the desired position in test-gas line 11. The tightening torque may be controlled via a torque wrench.

During the production process, housing 12 is first completed with external thread 34 and hexagon 35, and measuring element 13 including ceramic inserts 14, 15 and seal 16 are subsequently inserted into housing 12. To insert measuring element 13 into housing 12 during installation such that it

has a certain orientation with respect to the piercing point of external thread 34, a marking 36, which is oriented with respect to the piercing point of external thread 34, is made on housing 12. Marking 36 is designed as a small radial blind hole 37, which is made in hexagon 35, in the exemplary embodiment in Figure 7. Marking 36 is used to be able to fix measuring element 13 in housing 12 during the production process in a particularly simple manner such that the necessary orientation with respect to the piercing point of external thread 34 is achieved.

The present invention is not limited to the described sensor system having a lambda probe immersed in the exhaust-gas pipe of an internal combustion engine. Other sensors, e.g., temperature, moisture, or pressure sensors recording a corresponding parameter of the test gas, i.e., temperature, moisture, or pressure, may be used in the same manner instead of a lambda probe.

~~Abstract~~ ABSTRACT

~~Provided is a~~ A sensor system having a sensor (10) for  
5 measuring a gas parameter of a test gas via a measuring  
element (13), which is accommodated in a housing (12) and  
projects therefrom at least on the test gas side at a  
protruding section(131), and a test-gas line(11), through  
10 which the test gas flows, having a sensor insertion opening  
(25) and a receiving element (26) for the housing (12)  
surrounding the insertion opening (25) and attached to the  
test-gas line(11). For the purpose of assembly-independent,  
reproducible alignment of the measuring element (13) with  
15 respect to the test-gas flow during assembly of the sensor  
system, the receiving element (26) bears an internal  
thread(28), the piercing point of which is oriented with  
respect to the test-gas flow, and the housing (12) bears an  
external thread(34), which is able to be screwed into the  
20 internal thread (28) and the piercing point of which is  
oriented with respect to the measuring element(13). The  
housing (12) is fixed via a predefined tightening torque in  
the receiving element(26) ~~(Figure 7)~~.